

VIBGUARD[®] Advanced Condition Monitoring



VIBGUARD[®] – the safe system

Seamless monitoring for greater machine safety

PRÜFTECHNIK values safety! VIBGUARD[®] is a Condition Monitoring System that not only protects your machines from damage but also provides production security and improves the efficiency of your assets. Try it for yourself!


The facts about VIBGUARD®

- > 20 synchronous measurement channels
- Continuous data recording on every channel
- Tachometer pulse channels for triggered measurements
- Automatic check for sensor and cable defects
- Digital inputs and outputs
- Networkable (Ethernet, Modbus TCP)
- Compact and robust
- No active cooling required
- On board ring buffer for transient event capturing
- Supports Shock Pulse and Crest Factor for advanced bearing and gearbox monitoring

Intelligent data management

Every channel is able to measure continuously two time signals or one envelope curve signal and – at intervals of one second – up to 8 characteristic overall values, such as vibration severity and bearing condition. The 20 measurement channels supply sufficient data every day for seamless documentation of the machine status.

Intelligent data management ensures that important information is not lost and that the flow of information does not become overwhelming. This keeps the network load at an acceptable level and data can even be sent over a wireless connection without problems.



and a second second

Practical installation help

The terminal diagram shows the assignment of sensors and cables for the specific connection. A valuable reference during preparation for installation or for documentation.

VIBGUARD[®] – monitoring at top level

especially developed for your critical machines

VIBGUARD[®] – a new level of Online Condition Monitoring that for the first time allows critical machines with highly dynamic processes and complex monitoring tasks to be included in a reliability-oriented maintenance schedule.

VIBGUARD® is ...

▶ fast

CODD CODD CODD

Powerful processors, optimized measurement routines and intelligent data management place VIBGUARD[®] in the formula-1 class of online systems.

synchronous

VIBGUARD[®] measures continuously and simultaneously on up to 20 channels. This allows it to be used to monitor even complex machines with many variable operating parameters.

safe

VIBGUARD[®] protects your systems from sudden failure by seamless recording and evaluation of all status parameters.

autonomous

Data recording, evaluation and alarming are all included in the VIBGUARD[®] module.

modular

VIBGUARD[®] can be expanded at any time. Connect additional measurement channels or install additional VIBGUARD[®] modules in the switching cabinet.

flexible

The measurement channels can be configured to measure vibration and process values. The digital high and low pass filters can be set as required to derive the appropriate characteristic overall values.



Decessors

AB PREFECTION VISCUARD® Aced Monitoring System





... with many perspectives

VIBGUARD[®] Viewer adapts its interface to the application and displays only the content that you currently require for your work. For example, when measurement data is analyzed, the software shows the tree view of the machines and a measurement data diagram. For administration, configuration and reporting, the software shows the applicable views.

Analysis

Visualization and evaluation of measurement data

Configuration


Setup of measuring points and measurement tasks

Administration

Management of projects and system components

Report

Creation of interactive reports and tasks





Central system settings

The measurement tasks, the trigger and alarm conditions and additional parameters for data management are defined in the online manager for every channel.

All settings are hardware-based and do not require connection to the machine and measuring point hierarchy.


Interactive elements save time

A click of the mouse opens every referenced element. For example, click on a measurement and the corresponding diagram opens, click on a sensor and the sensor editor opens. ... for convenient and efficient working ...




A reliable partner on the PC

VIBGUARD[®] Viewer is the perfect companion for configuration of measurement channels, data analysis and reporting. A clear structure makes it very easy to use and provides a working environment where the user feels at home immediately. Advanced functions and the perfectly tailored user interface fulfill even the highest requirements.



Connection for power supply and communications

LED status displays



Convincing arguments

- Clearly arranged interface
- Context-dependent perspectives for improved overview and simple operation
- Multi-screen operation: separate windows can be distributed over multiple monitors
- Open reporting formats (HTML, DOC,...).
- Single or multi user version
- Kinematics model for calculation and management of characteristic machine frequencies – including complex systems
- Practical analytical tools: waterfall, cursor family, frequency markers, trend forecast, ...
- Advanced diagnostic features for turbomachinery: Orbit plot (unfiltered, 1st to 5th order), gap measurement, shaft centerline
- Export of raw data for further post processing
- Data analysis with reference to up to six operating states
- High operating speed with optimized data organization
- User administration with project-dependent roles
- Online manager for convenient configuration of measurement tasks
- ,To-do' outputs for tasks distribution and action-related system messages
- Compact housing suitable for standard rail
- Plug-in terminals for easy cable connections

Three models

- VIBGUARD[®] module for installation in a switching cabinet on a standard rail
- VIBGUARD[®] in the compact PRÜFTECHNIK protective housing
- VIBGUARD® in the standard PRÜFTECHNIK protective housing

VIBGUARD[®] is also available in a portable version for mobile troubleshooting. Please refer to the flyer VIBGUARD[®] portable for more details.

VIBGUARD® – part of the PRÜFTECHNIK strategy

VIBGUARD[®] forms an integral part of the PRÜFTECHNIK Condition Monitoring concept – consisting of handheld instruments and online monitoring systems. This allows the optimum monitoring solution that meets budgetary and technical requirements to be realized for each machine park.

Technical data - hardware modules - VIB 7.8...

| Measurement channels | 20 synchronous channels each with one ADC |
|----------------------|--|
| Dynamic range | 110 dB at 24 bits |
| FFT lines | standard: 6400 / analysis: 102400 |
| Channel monitoring | continuous over a separate signal path on every channel |
| Digital inputs | 4 |
| Speed inputs | 2 |
| Digital outputs | 4 relay outputs |
| Communication | TCP/IP, Modbus RTU |
| Comm. ports | Ethernet (100 Mbit); 2 x RS232 |
| Power supply | 24 VDC / 0.5 A |
| Memory capacity | 2 GB |
| Housing material | aluminium |
| Degree of protection | IP 20, in switching cabinet without protective housing IP 65, in protective housing |
| | |

PRÜFTECHNIK – proven technology for all industries

With our products, processes and services for alignment applications, condition monitoring and availability optimization, we help ensure that your machines run smoothly and generate an output of consistently high quality. This also includes systems for automatic process control and quality assurance that are integrated directly in your production process.

PRÜFTECHNIK consists of the following business areas



© Copyright 2014 by PRÜFTECHNIK AG. ISO 9001:2008 certified. VIBGUARD® and OMNITREND® are registered trademarks of PRÜFTECHNIK Dieter Busch AG. No copying or reproduction of this information, in any form whatsoever, may be undertaken without express written permission of PRÜFTECHNIK AG. The information contained in this leaflet is subject to change without further notice due to the PRÜFTECHNIK policy of continuous product development. PRÜFTECHNIK products are subject to patents granted or pending throughout the world.





PRÜFTECHNIK

Condition Monitoring GmbH Oskar-Messter-Str. 19-21 85737 Ismaning, Germany Tel.: +49 89 99616-0 Fax: +49 89 99616-300 info@pruftechnik.com www.pruftechnik.com